

Enhanced UL Adapter Kit

The Enhanced UL Adapter Kit is used with any standard AMETEK Brookfield Viscometer or DVNext Rheometer.

Features and Benefits

- Reduces measuring range to as low as 1 cP, depending on viscometer used
- Simple attachment to a standard AMETEK Brookfield Viscometer or DV3T/DVNext Rheometer
- Small sample size: 16 mL
- Cylindrical geometry provides defined shear rates for detailed product analysis
- A removable cap of low-density polyethylene can be considered disposable for one-time use if required
- Stainless steel parts are easily cleaned
- Quick and easy removal of chamber
- Magnetic Coupling System

What's Included

- Locating Channel Assembly
- Spindle with universal coupling nut
- Collar assembly with thumbwheel
- Water Jacket
- Chamber Tube
- Tube End Caps (Package of 6)



UL Adapter Ranges cP (mPa·s)

LVT, DVPLV**	DV2TLV DVNext***	RVT, DVPRV**	DV2TRV DVNext***	HAT, DVPHA**	DV2THA DVNext***	HBT, DVPHB**	DV2THB DVNext***
1.0-2K	1.0-2K	6.4-2K	3.0-2K	12.8-2K	6.0-2K	51.2-2K	24.0-2K

K=1 thousand

**Ranges also apply to previous DVE & DV1 series Viscometers

***Ranges also apply to previous DV3 series Rheometer